

散装线材 - 音频线 | 过机线

SOMMER CABLE 专业线材 - SC-ISOPOD

屏蔽层	AL/PT-foil + filler strand, tin-plated
屏蔽百分比	100 %
温度范围	最低-25 °C
温度范围	最高 70 °C
发货包装	200 米/卷
屏蔽层阻抗 每千米	75 Ohm
绝缘阻抗 每千米	> 200 MOhm

类 型 : SO-F22	SO-F50	SO-F22	SO-F22	SO-F22	SO-F22D	SO-F22	SO-F22F	SO-F22	SO-F22	SO-F22	SO-F22	SO-F22
结 (2LI2Y0.22 构 mm²)(ST)Y	(2LI2Y0,50 mm²)(ST)Y	(2LI2Y0.22 mm²)(ST)Y	(2LI2Y0.22 mm²)(ST)Y	(2LI2Y0.22 mm²)(ST)Y	(2LI2Y0.22 mm²)(ST)Y	(2LI2Y0.22 mm²)(ST)Y	(2LI2Y0.22 mm²)(ST)Y	(2LI2Y0.22 mm²)(ST)Y	(2LI2Y0.22 mm²)(ST)Y	(2LI2Y0.22 mm²)(ST)Y	(2LI2Y0.22 mm²)(ST)Y	(2LI2Y0.22 mm²)(ST)Y
外 PVC 3,3 皮,mm	PVC 4,2 mm	PVC 3,3 mm	PVC 3,3 mm	PVC 3,3 mm	PVC 3,3 mm	PVC 3,3 mm	FRNC 3,3 mm	PVC 3,3 mm	PVC 3,3 mm	PVC 3,3 mm	PVC 3,3 mm	PVC 3,3 mm
直 径												
A 24	21	24	24	24	24	24	24	24	24	24	24	24
W												
G												
(												
美												
标												



SOMMER CABLE

AUDIO - VIDEO - BROADCAST - MULTIMEDIA - HIFI

)												
芯 2 x 0,22 线 mm ² 数 量 x 内 径	2 x 0,50 mm ²	2 x 0,22 mm ²	2 x 0,22 mm ²	2 x 0,22 mm ²	2 x 0,22 mm ²	2 x 0,22 mm ²	2 x 0,22 mm ²	2 x 0,22 mm ²	2 x 0,22 mm ²	2 x 0,22 mm ²	2 x 0,22 mm ²	2 x 0,22 mm ²
铜 7 x 0,20 股 mm 每 芯 线	7 x 0,30 mm	7 x 0,20 mm	7 x 0,20 mm	7 x 0,20 mm	7 x 0,20 mm	7 x 0,20 mm	7 x 0,20 mm	7 x 0,20 mm	7 x 0,20 mm	7 x 0,20 mm	7 x 0,20 mm	7 x 0,20 mm
绝 PE 1,12 缘 mm 外 皮	PE 1,5 mm	PE 1,12 mm	PE 1,12 mm	PE 1,12 mm	PP 1,3 mm	PE 1,12 mm	PE 1,12 mm	PE 1,12 mm	PE 1,12 mm	PE 1,12 mm	PE 1,12 mm	PE 1,12 mm
电 0,05 kWh 功 每 米	0,07 kWh	0,05 kWh	0,05 kWh	0,05 kWh	0,05 kWh	0,05 kWh	on request	0,05 kWh	0,05 kWh	0,05 kWh	0,05 kWh	0,05 kWh
重 16 g 量 每 米	19 g	16 g	16 g	16 g	16 g	16 g	16 g	16 g	16 g	16 g	16 g	16 g
颜  灰	 灰	 黑	 蓝	 红	 灰	 黄	 黑	 白	 绿	 橙	 紫	 棕



东汇传播拓展有限公司

色												
类 ---	---	---	---	---	110 Ohm	---	FRNC	---	---	---	---	---
型												
线 74 pF	100 pF	74 pF	74 pF	74 pF	74 pF	74 pF	74 pF	74 pF	74 pF	74 pF	74 pF	74 pF
芯												
间												
电												
容												
每												
米												
线 143 pF	160 pF	143 pF	143 pF	143 pF	143 pF	143 pF	143 pF	143 pF	143 pF	143 pF	143 pF	143 pF
屏												
蔽												
层												
间												
电												
容												
每												
米												
容 88 Ohm	39 Ohm	88 Ohm	88 Ohm	88 Ohm	75 Ohm	88 Ohm	88 Ohm	88 Ohm	88 Ohm	88 Ohm	88 Ohm	88 Ohm
抗												
每												
米												
订 200-0406	201-0406	200-0401	200-0402	200-0403	500-0406	200-0407	200-0401F	200-0400	200-0404	200-0405	200-0408	200-040N
货												
号.												

