

散装线材 - 视频 | RG/U 同轴电缆 50 Ohm

SOMMER CABLE - SC-CLASSIC SERIES MKII

包装 100 m ring/500 m roll

类型:	RG8/U	RG58C/U	RG58C/U LL	RG174A/U	RG213/U	RG214/U	RG316/U	RG58C/U	RG213/LL
外皮, 直径	PVC 9,5 mm	PVC 4,95 mm	PVC 5,0 mm	PVC 2,8 mm	PVC 10,3 mm	PVC 10,8 mm	PTFE 2,5 mm	FRNC 4,95 mm	PVC 10,2 mm
AWG	13	20	18	26	12	12	25	20	10
内径	2,7 mm ²	0,48 mm ²	---	0,14 mm ²	3,09 mm ²	3,09 mm ²	0,16 mm ²	0,48 mm ²	5,5 mm ²
直径	1,85 mm	0,78 mm	1,02 mm	0,42 mm	1,98 mm	1,98 mm	0,45 mm	0,78 mm	2,65 mm
铜股 每芯线	---	---	solid copper 1 x 1,02 mm	---	---	---	---	---	---
铜股 每芯线	copper, bare 7 x 0,70 mm	copper, tin-plated 19 x 0,18 mm	---	wire 7 x 0,16 mm	copper 7 x 0,75 mm	copper silver-plated 7 x 0,75 mm	Staku silver-coated 7 x 0,17 mm	copper, tin-plated 19 x 0,18 mm	copper 7 x 1,0 mm
绝缘外皮	PE 6,4 mm	PE 2,95 mm	Foam/skin-PE 2,95 mm	PE 1,5 mm	PE 7,3 mm	PE 7,25 mm	PTFE 1,52 mm	PE 2,95 mm	Foam/skin-PE 7,25 mm
屏蔽层	copper braiding, bare	copper braiding, tin-plated	copper braiding tin-plated + AL-foil	copper braiding, tin-plated	copper braiding, bare	2 x copper braiding silve 红	copper braiding silve 红	copper braiding, tin-plated	copper braiding, bare + copper foil
屏蔽层 因数	92 %	92 %	92 %	92 %	92 %	95 %	95 %	92 %	100 %
温度范围	最低-25 °C	最低-25 °C	最低-25 °C	最低-25 °C	最低-25 °C	最低-25 °C	最低-35 °C	最低-25 °C	最低-25 °C
	最高 70 °C	最高 70 °C	最高 70 °C	最高 70 °C	最高 70 °C	最高 70 °C	最高 80 °C	最高 70 °C	最高 70 °C
电功 每米	0,59 kWh	0,15 kWh	0,15 kWh	0,11 kWh	0,70 kWh	0,73 kWh	0,12 kWh	0,15 kWh	0,71 kWh



重量 每米	128 g	38 g	38 g	11 g	159 g	205 g	15 g	38 g	166 g
匹配插座	BNC213-T	BNC58	BNC58	BNC174	BNC213	---	BNC0.3/1.8	BNC58	BNC213LL-T
	---	---	---	SMA174, SMB174	---	---	SMAF316-AU	---	---
	---	---	---	---	---	---	SMAM316-AU	---	---
	---	---	---	---	---	---	SMB174	---	---
颜色	■ 黑	■ 黑	■ 黑	■ 黑	■ 黑	■ 黑	□ 透明	■ 黑	■ 黑
线屏蔽层间 电容 每米	101 pF	101 pF	82 pF	101 pF	101 pF	101 pF	95 pF	101 pF	82 pF
浪涌阻抗 每 千米	+/-3% 50 Ohm	+/-2% 50 Ohm	+/-3% 50 Ohm	+/-2% 50 Ohm	+/-2% 50 Ohm	+/-2% 50 Ohm	+/-3% 50 Ohm	+/-2% 50 Ohm	+/-2% 50 Ohm
速率因数	0,66	0,66	0,66	0,66	0,66	0,66	0,66	0,66	0,81
阻尼 每百米 (20 °C)	100 MHz: 7,8 dB	100 MHz: 15,3 dB	100 MHz: 10,3 dB	100 MHz: 27,4 dB	100 MHz: 7,0 dB	100 MHz: 6,7 dB	100 MHz: 28,0 dB	100 MHz: 15,3 dB	100 MHz: 4,3 dB
	200 MHz: 10,6 dB	200 MHz: 22,8 dB	200 MHz: 15,2 dB	200 MHz: 40,7 dB	200 MHz: 9,2 dB	200 MHz: 9,8 dB	200 MHz: 40,0 dB	200 MHz: 22,8 dB	200 MHz: 6,7 dB
	500 MHz: 17,2 dB	500 MHz: 37,0 dB	500 MHz: 21,5 dB	500 MHz: 73,0 dB	500 MHz: 16,7 dB	500 MHz: 16,5 dB	500 MHz: 68,0 dB	500 MHz: 37,0 dB	500 MHz: 9,8 dB
	800 MHz: 24,0 dB	800 MHz: 48,8 dB	800 MHz: 30,1 dB	800 MHz: 91,8 dB	800 MHz: 20,0 dB	800 MHz: 23,0 dB	800 MHz: 90,0 dB	800 MHz: 48,8 dB	800 MHz: 12,8 dB
	---	---	---	---	1000 MHz: 23,0 dB	1000 MHz: 26,2 dB	---	---	1000 MHz: 15,0 dB
	---	---	---	---	---	---	---	---	1350 MHz: 16,9 dB
	---	---	---	---	---	---	---	---	1500 MHz: 18,1 dB



	---	---	---	---	---	---	---	---	3000 MHz: 32,8 dB
	---	---	---	---	---	---	---	---	2000 MHz: 21,5 dB
	---	---	---	---	---	---	---	---	2400 MHz: 24,1 dB
订货号.	<u>600-0511</u>	<u>600-0401</u>	<u>600-0401LL</u>	<u>600-0501</u>	<u>600-0551</u>	<u>600-0571</u>	<u>600-0549</u>	<u>600-0401F</u>	<u>600-0551LL</u>

