

散装线材 - 视频 | Sat cable

SOMMER CABLE - SC-ASTRAL

铜股 每芯线	solid copper mm
屏蔽层	copper braiding tin-plated + AL-foil
屏蔽层 因数	100 %
温度范围	最低-20 °C
温度范围	最高 70 °C
颜色	☐ 白
浪涌阻抗	(+/-3 %) 75 Ohm

类型:	(0.7/2.9)	(2x0.75/3.4)	4x(0.7/2.9)	(0.5/2.0)
结构	(0.7/2.9) 90 dB	2x(0.75/3.4) 75 dB	4x(0.7/2.9) 90dB	(0.5/2.0)>75dB
内径	1 x 0,65 mm	2 x 0,75 mm	4 x 0,65 mm	1 x 0,5 mm
外皮, 直径	PVC 4,5 mm	PVC 2 x 5,5 mm	PVC 12,5 mm	PVC 3,6 mm
AWG	22	21	22	24
绝缘外皮	Foam/skin-PE 3,0 mm	Foam/skin-PE 3,4 mm	Foam/skin-PE 3,0 mm	Foam/skin-PE 2,0 mm
电功 每米	0,12 kWh	0,31 kWh	0,58 kWh	0,11 kWh
最小弯曲半径	---	---	---	19 mm
重量 每米	29 g	70 g	52 g	20 g
包装	100 m ring/500 m roll	100 m ring/500 m roll	100 m ring/500 m roll	100 m ring
匹配插座	FM0.7/2.9	FM0.75/3.4	FM0.7/2.9	---



屏蔽层	> 90 dB	> 75 dB	> 90 dB	> 75 dB
D.C. 阻抗 每千米	inner conductor 52 Ohm	inner conductor 40 Ohm	inner conductor 52 Ohm	inner conductor 60 Ohm
	outer conductor 42 Ohm	outer conductor 25 Ohm	outer conductor 42 Ohm	outer conductor 51 Ohm
阻尼 每百米 (20 °C)	100 MHz: 8,8 dB	100 MHz: 7,4 dB	100 MHz: 8,8 dB	100 MHz: 15,7 dB
	300 MHz: 16,5 dB	300 MHz: 15,0 dB	300 MHz: 16,5 dB	300 MHz: 28,8 dB
	450 MHz: 21,2 dB	450 MHz: 19,2 dB	450 MHz: 21,2 dB	450 MHz: 31,6 dB
	862 MHz: 28,2 dB	862 MHz: 26,0 dB	862 MHz: 28,2 dB	862 MHz: 44,4 dB
	1000 MHz: 31,0 dB	1000 MHz: 28,9 dB	1000 MHz: 31,0 dB	1000 MHz: 48,0 dB
	1750 MHz: 42,5 dB	1750 MHz: 40,4 dB	1750 MHz: 42,5 dB	1750 MHz: 65,1 dB
	2250 MHz: 51,3 dB	2250 MHz: 50,1 dB	2250 MHz: 51,3 dB	2250 MHz: 75,6 dB
	2500 MHz: 53,6 dB	2500 MHz: 52,2 dB	2500 MHz: 53,6 dB	2500 MHz: 79,1 dB
	2150 MHz: 46,5 dB	2150 MHz: 45,1 dB	2150 MHz: 46,3 dB	2150 MHz: 70,5 dB
订货号.	<u>600-0970</u>	<u>600-0980</u>	<u>600-0990</u>	<u>600-0920</u>

